

FRONT-TILLER



- 2 rows of harrow sections with good clearance.
- Up to 300 mm working depth.
- 2 types of tines:
 - Tines with double-stranded springs 40x40 mm, 0-30 cm working depth.
 - Automatic with spring release for 560 kg, 0-30 cm working depth.
- Compact machine.
- Oblong hole for top link.
- Spindle adjustable strong depth wheels.

MACHINES

Work Width, m	Description	Weight, kg	Item Number
3.00	9 tines, double-stranded springs	1,090	67510-15
3.00	9 tines, with spring release	1,405	67510-05
4.00	13 tines, double-stranded springs	1,240	67510-20
4.00	13 tines, with spring release	1,695	67510-10

STANDARD EQUIPMENT

- Pivotal depth wheels, 2 pieces 10.0/80x12 – 10 PLY.
- 50x25 mm reversible wearing point.
- Pins and locking pins.

EXTRA EQUIPMENT

Description	Weight, kg	Item Number
LED marking lights with clear and red glass	4	67510-50
Set of reflective warning boards (2 pieces)	8	67055-74
Edge equipment set w/adjustable discs	60	67510-55
75 x 12 mm reversible and high adjustable wearing point. (Additional price per tine)	-	67510-60
75 x 19 mm reversible and high adjustable wearing point. ((Additional price per meter)	-	67510-61
Tip with tungsten with twisted mould board (Additional price per meter)	-	67510-62
Goose foot tip (Additional price per meter)	-	67510-63
Goose-foot tip with hardmetal (Additional price per meter)	-	67510-64