

VIP-ROLLER NG



- Compact construction of sectional tubes.
- Low transport height – stable and safe transport.
- Simple transfer between transport and working position.
- Hydraulic system released during transport/storage.
- 60 mm axles, special quality, and triple-sealed ball bearings.
- Transport width of max. 2.45 m.

MACHINES

Work Width, m	Ring Type	No. of Rings	No. of Spokes	Power Req., HP	Weight, kg	Item Number
4.50	510 mm/21" Cambridge ^{1*}	87	3	60-80	2,120	63201-51
4.50	510 mm/21" Cambridge ^{1*}	87	8	60-80	2,220	63201-46
4.50	560 mm/22.5" Cambridge ^{1*}	87	9	70-90	2,500	63201-54
4.50	620 mm/24" Cambridge ^{1*}	87	10	70-90	2,770	63201-62
4.50	450/500 mm Star ring ^{•/1*}	84	-	60-80	2,120	63201-56
4.50	550/600 mm Star ring ^{•/1*}	84	-	70-90	2,530	63201-57
4.50	550 mm Cam ring ^{1*}	30	-	60-80	1,470	63201-55
4.50	485-530 mm Crosskill ^{1*}	45	-	60-80	1,940	63201-53
4.50	550-600 mm Crosskill ^{1*}	45	-	70-90	2,420	63201-63
4.50	500 mm 2D-Corrugated ^{1*}	57	8	60-80	1,950	63201-50
4.50	550 mm 2D-Corrugated ^{1*}	57	9	70-90	2,190	63201-59
4.50	600 mm 2D-Corrugated ^{1*}	57	10	70-90	2,340	63201-60
5.40	510 mm/21" Cambridge ^{1*}	105	3	70-90	2,520	63202-51
5.40	510 mm/21" Cambridge ^{1*}	105	8	70-90	2,650	63202-46
5.40	560 mm/22.5" Cambridge ^{1*}	105	9	80-100	3,060	63202-54
5.40	620 mm/24" Cambridge ^{1*}	105	10	80-100	3,200	63202-62
5.40	450/500 mm Star ring ^{•/1*}	98	-	70-90	2,570	63202-56
5.40	550/600 mm Star ring ^{•/1*}	98	-	80-100	3,100	63202-57
5.40	550 mm Cam ring ^{1*}	36	-	70-90	1,840	63202-55
5.40	485-530 mm Crosskill ^{1*}	54	-	70-90	2,410	63202-53
5.40	550-600 mm Crosskill ^{1*}	54	-	80-100	2,970	63202-63
5.40	500 mm 2D-Corrugated ^{1*}	69	8	70-90	2,390	63202-50
5.40	550 mm 2D-Corrugated ^{1*}	69	9	80-100	2,690	63202-59
5.40	600 mm 2D-Corrugated ^{1*}	69	10	80-100	2,930	63202-60
6.30	510 mm/21" Cambridge ^{1*}	123	3	80-100	2,860	63203-51
6.30	510 mm/21" Cambridge ^{1*}	123	8	80-100	3,050	63203-46
6.30	560 mm/22.5" Cambridge ^{1*}	123	9	100-120	3,520	63203-54
6.30	620 mm/24" Cambridge ^{1*}	123	10	100-120	4,000	63203-62
6.30	450/500 mm Star ring ^{•/1*}	120	-	80-100	2,920	63203-56
6.30	550/600 mm Star ring ^{•/1*}	120	-	120-120	3,680	63203-57
6.30	550 mm Cam ring ^{1*}	42	-	80-100	2,030	63203-55
6.30	485-530 mm Crosskill ^{1*}	63	-	80-100	2,690	63203-53
6.30	550-600 mm Crosskill ^{1*}	63	-	100-120	3,300	63203-63
6.30	500 mm 2D-Corrugated ^{1*}	78	8	80-100	2,750	63203-50
6.30	550 mm 2D-Corrugated ^{1*}	78	9	90-110	3,060	63203-59
6.30	600 mm 2D-Corrugated ^{1*}	78	10	90-110	3,200	63203-60
6.30	610 mm Plain Roller ^{1*/2*}	-	-	90-110	2,050 3,670	63203-61

^{1*}Requires 2 double-acting oil outlets

^{2*}Weight designation: Respectively without and with water.

• Steel cast ring, 8 year breakage warranty

MACHINES (CONTINUED)

Work Width, m	Ring Type	No. of Rings	No. of Spokes	Power Req., HP	Weight, kg	Item Number	
7.30	510 mm/21" Cambridge	1*	143	3	100-120	3,440	63204-51
7.30	510 mm/21" Cambridge	1*	143	8	100-120	3,650	63204-46
7.30	560 mm/22.5" Cambridge	1*	143	9	120-140	4,240	63204-54
7.30	620 mm/24" Cambridge	1*	143	10	120-140	4,390	63204-62
7.30	450/500 mm Star ring	•/1*	140	-	100-120	3,570	63204-56
7.30	550/600 mm Star ring	•/1*	140	-	120-140	4,490	63204-57
7.30	550 mm Cam ring	1*	48	-	100-120	2,520	63204-55
7.30	485-530 mm Crosskill	1*	73	-	100-120	3,270	63204-53
7.30	550-600 mm Crosskill	1*	73	-	120-140	4,190	63204-63
7.30	500 mm 2D-Corrugated	1*	90	8	100-120	3,330	63204-50
7.30	550 mm 2D-Corrugated	1*	90	9	110-130	3,670	63204-59
7.30	600 mm 2D-Corrugated	1*	90	10	110-130	3,820	63204-60
7.60	510 mm/21" Cambridge	1*	151	3	100-120	3,564	63206-51
7.60	510 mm/21" Cambridge	1*	151	8	100-120	3,804	63206-46
7.60	560 mm/22.5" Cambridge	1*	151	9	120-140	4,418	63206-54
7.60	620 mm/24" Cambridge	1*	151	10	120-140	4,568	63206-62
7.60	450/500 mm Star ring	•/1*	148	-	100-120	3,710	63206-56
7.60	550/600 mm Star ring	•/1*	148	-	120-140	4,640	63206-57
7.60	550 mm Cam ring	1*	45	-	100-120	2,588	63206-55
7.60	485-530 mm Crosskill	1*	79	-	100-120	3,340	63206-53
7.60	550-600 mm Crosskill	1*	79	-	120-140	4,290	63206-63
7.60	500 mm 2D-Corrugated	1*	99	8	100-120	3,440	63206-50
7.60	550 mm 2D-Corrugated	1*	99	9	110-130	3,792	63206-59
7.60	600 mm 2D-Corrugated	1*	99	10	110-130	3,950	63206-60
8.20	510 mm/21" Cambridge	1*	157	3	120-140	3,860	63205-51
8.20	510 mm/21" Cambridge	1*	157	8	120-140	4,000	63205-46
8.20	560 mm/22.5 Cambridge	1*	157	9	130-160	4,510	63205-54
8.20	620 mm/24" Cambridge	1*	157	10	130-160	5,010	63205-62
8.20	450/500 mm Star ring	•/1*	152	-	120-140	3,990	63205-56
8.20	550/600 mm Star ring	•/1*	152	-	130-160	4,930	63205-57
8.20	550 mm Cam ring	1*	55	-	120-140	2,820	63205-55
8.20	485-530 mm Crosskill	1*	81	-	120-140	3,690	63205-53
8.20	550-600 mm Crosskill	1*	81	-	130-160	4,710	63205-63
8.20	500 mm 2D-Corrugated	1*	102	8	120-140	3,650	63205-50
8.20	550 mm 2D-Corrugated	1*	102	9	120-150	3,910	63205-59
8.20	600 mm 2D-Corrugated	1*	102	10	120-150	4,160	63205-60

*Requires 2 double-acting oil outlets

• Steel cast ring, 8 year breakage warranty

STANDARD EQUIPMENT

- Adjustable jack stand.
- Towing eye, secured by bolts, item no. 630757028.
- Wheels :
 - 4.50 m – 5.40 m: 10.0/75x15.3, 10 PLY.
 - 6.30 m – 8.20 m: 11.5/80x15.3, 14 PLY.
- Triple-sealed ball bearings.
- Parking device for hydr. hoses.

EXTRA EQUIPMENT

Description	Weight, kg	Item Number	
LED lights cpl. with wire and socket, mounted on 4.50 -5.40 m		63201-22	
LED lights cpl. with wire and socket, mounted on 6.30-7.30-7.60-8.20 m		63203-22	
Hydraulic supporting leg for 4.50-8.20 m (Additional price)	1*	15	63053-40
Mechanical double change-over valve, mounted on drawbar, for tractors requiring another double-acting oil outlet	5	690207102	
Electrically operated double change-over valve, with contact to the cab, for tractors with too few double-acting oil outlets.	8	690207105	
Drawbar extension, 500 mm for 4.50 / 5.40 m	42	630779000	
Drawbar extension, 500 mm for 6.30 / 7.30 / 7.60 / 8.20 m	42	630779020	
Air brakes, factory-mounted	18	63098-07	
Hydraulic brakes, 1-circuit, factory-mounted	7	63098-08	
Hydraulic brakes, 2-circuit, factory-mounted	-	63098-09	
Stone box set (additional 2 pieces) for 4.50 / 5.40 / 6.30 / 7.30 / 7.60 / 8.20 m	-	63201-20	
Weight transition kit (SAT-system) for 4.50 – 5.40 m.	-	63201-21	
Weight transition kit (SAT-system) for 6.30 – 8.20 m.	-	63203-23	
Wheel 11.5/80 x 15.3, 14 PLY, only for Vip-Roller NG 4.50 and 5.40 m. (Additional price per set)	-	63080-10	
Wheels 400/60 x 15.5 – 16 PLY, only for Vip-Roller NG 6.30, 7.30, 7.60 and 8.20 m (all ring types). NB: Transport width: 2.56 m. (Additional price per set)	-	63080-09	
Electronic area counter, mounted	-	0539317	

*Requires 1 double-acting oil outlet

EXTRA EQUIPMENT (CONTINUED)

CAST STEEL RINGS

Description	Weight, kg	Item Number
510 mm/21" Cambridge / 550 mm 2D-Corrugated. Steel cast quality. 8 spokes. Recommended in a non-ploughed syst. and in extreme conditions. (Add. price per m)	+ 8 per m	690150078
560 mm/22.5" Cambridge / 550 mm 2D-Corrugated. Steel cast quality. 9 spokes. Recommended in a non-ploughed syst. and in extreme conditions. (Add. price per m)	+ 10 per m	690150077
620 mm/24" Cambridge / 600 mm 2D-Corrugated. Steel cast quality. 10 spokes. Recommended in a non-ploughed syst. and in extreme conditions. (Add. price per m)	+ 10 per m	690150118

8 YEAR WARRANTY ON STEEL CAST RINGS



SPRING-BOARD

Work Width, m	Description	No. of Tines	Power Req., HP	Weight, kg	Item Number
4.50	Spring-Board	20	+20	420	63201-00
5.40	Spring-Board	22	+25	485	63202-00
6.30	Spring-Board	24	+30	550	63203-00
7.30	Spring-Board	28	+35	630	63204-00
7.60	Spring-Board	-	+35	655	63206-00
8.20	Spring-Board	32	+40	695	63205-00
-	Edge equipment set for Spring-Board tines	-	-	5	63301-00
4.50	Spring-Board with slicing plates	-	-	-	63201-05
5.40	Spring-Board with slicing plates	-	-	-	63202-05
6.30	Spring-Board with slicing plates	-	-	-	63203-05
7.30	Spring-Board with slicing plates	-	-	-	63204-05
7.60	Spring-Board with slicing plates	-	-	-	63206-05
8.20	Spring-Board with slicing plates	-	-	-	63205-05
4.50	Spring-Board with Ø16 longfinger tines	-	-	-	63201-10
5.40	Spring-Board with Ø16 longfinger tines	-	-	-	63202-10
6.30	Spring-Board with Ø16 longfinger tines	-	-	-	63203-10
7.30	Spring-Board with Ø16 longfinger tines	-	-	-	63204-10
7.60	Spring-Board with Ø16 longfinger tines	-	-	-	63206-10
8.20	Spring-Board with Ø16 longfinger tines	-	-	-	63205-10
TRANSVERSE LOCKING SYSTEM - CONNECTS THE SPRING-BOARD TINES					
4.50	Complete set for Spring-Board	-	-	55	63201-15
5.40	Complete set for Spring-Board	-	-	64	63202-15
6.30	Complete set for Spring-Board	-	-	74	63203-15
7.30	Complete set for Spring-Board	-	-	86	63204-15
7.60	Complete set for Spring-Board	-	-	89	63206-15
8.20	Complete set for Spring-Board	-	-	97	63205-15



"EASY-CHANGE" QUICK CHANGE SYSTEM OF WEAR POINTS INCL. ONE SET OF FLAT WEAR POINTS AND ONE SET OF SLICING PLATE POINTS WITH 3 TINES.

Description	Item Number
Additional price per tine in relation to standard Spring-Board	63302-00
Price per tine for retrofitting	63302-01

WHEEL TRACK ERADICATOR FRAME FOR LIFT

Description	Item Number
3.00 m. three-point mounted, 6 tines (65x12 mm)	67701-00
4.00 m. three-point mounted, 8 tines (65x12 mm)	67702-00



Wheel Track Eradicator Frame for Lift.