

TRIPLE-TILLER AIRY



- Optimal cultivating with only 25 cm row spacing.
- 3 rows of harrow section with good clearance with 85 cm frame height, 75 cm tine spacing and 70 cm bar spacing.
- Eradicator discs, standard equipment, w/centre spindle adjustment, stone protected by rubber suspension.
- Spring-loaded, spindle adjustable long finger after-harrow is standard on the harrow.
- Three-point linkage with category 3 pins and category 2 distance.
- 4 tine options:
 - Spring tine double-twisted 35 x 35 mm for 2.50 - 3.50 m models. Work depth: 0 - 20 cm.
 - Spring tine double-twisted 40 x 40 mm for 4.00 - 6.00 m models. Work depth: 0 - 30 cm.
 - Shear bolt - preloaded for 2,550 kg. Work depth: 0 - 30 cm.
 - Automatic w/spring /auto reset preloaded for 560 kg. Work depth: 0 - 30 cm.

MACHINES

Work Width, m	Type	Stone Protection	No. of Tines	Power Req., HP	Lifting Req., kg	Transport Width, m	Weight, kg	Item Number
2.50	Rigid, 1-section	Spring tine	10	80-160	2,250	2.50	1,250	4522501
2.50	Rigid, 1-section	Shear bolt	10	80-160	2,250	2.50	1,250	4522505
2.50	Rigid, 1-section	Automatic	10	80-160	2,250	2.50	1,250	4522503
3.00	Rigid, 1-section	Spring tine	12	100-200	2,450	3.00	1,360	4523001
3.00	Rigid, 1-section	Shear bolt	12	100-200	2,450	3.00	1,360	4523005
3.00	Rigid, 1-section	Automatic	12	100-200	2,450	3.00	1,360	4523003
3.50	Rigid, 1-section	Spring tine	14	120-240	2,650	3.50	1,470	4523501
3.50	Rigid, 1-section	Shear bolt	14	120-240	2,650	3.50	1,470	4523505
3.50	Rigid, 1-section	Automatic	14	120-240	2,650	3.50	1,470	4523503
4.00	Rigid, 1-section	Spring tine	16	140-250	2,850	4.00	1,580	4524001
4.00	Rigid, 1-section	Shear bolt	16	140-250	2,850	4.00	1,580	4524005
4.00	Rigid, 1-section	Automatic	16	140-250	2,850	4.00	1,580	4524003
4.00	Foldable, 2-section	Spring tine	1* 16	140-250	4,020	2.48	2,230	4524101
4.00	Foldable, 2-section	Shear bolt	1* 16	140-250	4,020	2.48	2,230	4524105
4.00	Foldable, 2-section	Automatic	1* 16	140-250	4,020	2.48	2,230	4524103
5.00	Foldable, 2-section	Spring tine	1* 20	160-280	4,220	2.48	2,340	4525101
5.00	Foldable, 2-section	Shear bolt	1* 20	160-280	4,220	2.48	2,340	4525105
5.00	Foldable, 2-section	Automatic	1* 20	160-280	4,220	2.48	2,340	4525103
6.00	Foldable, 2-section	Spring tine	1* 24	180-300	4,410	2.48	2,450	4526101
6.00	Foldable, 2-section	Shear bolt	1* 24	180-300	4,410	2.48	2,450	4526105
6.00	Foldable, 2-section	Automatic	1* 24	180-300	4,410	2.48	2,450	4526103

*Requires 1 double-acting oil outlet.



4.00 m Triple-Tiller Airy with spring tines.

STANDARD EQUIPMENT

- 75 x 12 mm reversible and height adjustable concave wearing point (double curved).
- Ø410 mm scalloped eradicator discs with centre spindle adjustment, stone protected by rubber suspension.
- Spring-loaded and spindle adjustable long finger after-harrow after the eradicator discs.
- Autom. transport locking devices, operated hydr. together w/the folding function.
- Wheels:
 - 2.50 / 3.00 / 3.50 / 4.00 m. rigid 1-section: 2 pcs. 200/60 x 14.5 – 10 PLY.
 - 4.00 / 5.00 w/hydr. folding: 2 pcs. 200/60 x 14.5 – 10 PLY.
 - 6.00 m, 2-section w/hydr. folding: 4 pcs. 200/60 x 14.5 – 10 PLY.

EXTRA EQUIPMENT

Work Width, m	Description	Weight, kg	Item Number
2.50 - 4.00	LED lights complete with wire and socket mounted on 1-section models	3	4519510
4.00 - 6.00	LED lights with wire and socket, mounted on 2-section models	3	4519515
2.50 - 6.00	Set of reflective warning boards (2 pieces)	8	67055-74
2.50 - 6.00	Narrow wear point, 50 mm x 25 mm – Same price as for standard point	-	4509310
2.50 - 6.00	Concave reversible tip - 19 mm thickness (Additional price per meter)	-	4509306
2.50 - 6.00	Tip with tungsten with twisted mould board (Additional price per meter)	-	4509309
2.50 - 6.00	Goose foot tip (Additional price per meter)	-	4509308
2.50 - 6.00	Goose-foot tip with hardmetal (Additional price per meter)	-	4509307
-	Edge disc set, fold-up (Price per set)	33	4519452
4.00 - 5.00	Extra depth wheel, 2 pcs. 200/60 x 14.5	275	4519752
2.50 - 3.00	Hydraulic lifting of leveling discs (Additional price)	^{1*} -	4519460
3.50 - 6.00	Hydraulic lifting of leveling discs (Additional price)	^{1*} -	4519461

^{1*}Requires 1 double-acting oil outlet.

QUICK CHANGE KIT - INCL. ONE SET OF CHISEL POINTS 75 MM WIDE AND ONE SET OF 260 MM WIDE WING SHARES.			
Work Width, m	Description	Weight, kg	Item Number
2.50	"Quick change kit" with twisted mould board, factory-mounted (Additional price)	16	4509025
3.00	"Quick change kit" with twisted mould board, factory-mounted (Additional price)	20	4509030
3.50	"Quick change kit" with twisted mould board, factory-mounted (Additional price)	23	4509035
4.00	"Quick change kit" with twisted mould board, factory-mounted (Additional price)	26	4509040
5.00	"Quick change kit" with twisted mould board, factory-mounted (Additional price)	33	4509050
6.00	"Quick change kit" with twisted mould board, factory-mounted (Additional price)	39	4509060
2.50 - 6.00	"Quick change kit" with twisted mould board. (Left) retrofitting (Additional price per meter)	-	4509019
2.50 - 6.00	"Quick change kit" with twisted mould board. (Right) retrofitting (Additional price per meter)	-	4509020
2.50	"Quick change kit" with straight mould board, factory-mounted (Additional price)	19	4509225
3.00	"Quick change kit" with straight mould board, factory-mounted (Additional price)	23	4509230
3.50	"Quick change kit" with straight mould board, factory-mounted (Additional price)	27	4509235
4.00	"Quick change kit" with straight mould board, factory-mounted (Additional price)	30	4509240
5.00	"Quick change kit" with straight mould board, factory-mounted (Additional price)	38	4509250
6.00	"Quick change kit" with straight mould board, factory-mounted (Additional price)	45	4509260
2.50 - 6.00	"Quick change kit" with straight mould board. retrofitting (Additional price per meter)	-	4509220

MOUNTING SET FOR MULTI-SEEDER INCL. MOUNTING ON NEW TRIPLE-TILLER AIRY - MAX. 300 KG LOAD IN FINE SEED HOPPER. PRICES AND INFO ON MULTI-SEEDER			
Work Width, m	Type	Item Number - 8 Outlets	
2.50 - 4.00	Rigid	4509930	
4.00 - 6.00	Foldable	4509940	